



# E-Z MIX INC.

## PMP DECK MUD

Product Name: **PMP DECK MUD**

Data sheet 1203-95  
September 2018

**Product Description:** PMP Deck Mud is a dry, factory blended mortar specifically designed for use by tile and masonry contractors. The product is a preblended mix of washed plaster sand and Type II/V cement. Preblending allows the cement to thoroughly coat the sand particles thus producing a stronger than jobsite mix. The mortar bed is compatible with cement based and most water based latex adhesives. Standard mix design is 4:1 by weight. Special mix designs available.



**Application:** Mix PMP Deck Mud with only enough clean, potable water to form a ball when compacted in your hands. Compact and screed into place. Allow for proper cure prior to application of any adhesives. Do not try to accelerate cure with fans. Bonding mortar should be tested for suitability with PMP Deck Mud. Do not use epoxy mortars without consulting the manufacturer cure time and compatibility concerns.

**Limitations:**

- Do not apply when temperature is below or may fall below 40°F prior to curing.
- Do not overwater or overmix.
- Do not accelerate curing time with fans.
- Consult manufacturer prior to using epoxy bonding mortars.

**Uses:** PMP Deck Mud is a leveling mortar underlayment for all types of pavers, tile and marble on floors and countertops.

**Advantages:**

- Quality control - a consistent batch every time.
- Convenience of handling and transporting one product.
- Excellent for multi-story and difficult access jobs.

**Packaging:** Available in 75 lb. paper bags, 3000 lb. bulk bags or bulk. Information on silos and bulk systems available upon request.

**Technical Data:** PMP Deck Mud conforms to the volume composition for floor applications of ANSI A108.1A 2.2., IBC and CBC Table 2103.2.3, CBC Table 2103A.2.3, and L.A. City approval RR24968.

**Coverage:** Each 75 lb. bag will yield approximately 9.6 Sq Ft at 1 inch thickness.

**Warranty:** The technical information and usage statements are based on our best knowledge. The contents of this specification sheet are presented for informational purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.


**CAUTION:** Avoid direct contact where possible and wash exposed skin areas promptly. If any material gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. See Safety Data Sheet.

**For technical support contact:**  
[www.EZMixInc.com](http://www.EZMixInc.com)      [jjara@EZMixInc.com](mailto:jjara@EZMixInc.com)

**Corporate Office:**  
11374 Tuxford St.  
Sun Valley, CA 91352  
(818) 767-8576

**Sun Valley Plant:**  
11450 Tuxford St.  
Sun Valley, CA 91352  
(818) 768-0568

**Rialto Plant:**  
3355 Industrial Rd.  
Rialto, CA 92316  
(909) 874-7686

 **WARNING:** This product can expose you to chemicals including Chromium (hexavalent compounds), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

©2018 E-Z Mix, Inc.