



E-Z MIX INC.

PMP SPEC CONCRETE 3000

for use in masonry grouting applications

Product Name: **PMP SPEC CONCRETE 3000**

Data sheet 2090-15
September 2018

Product Description: PMP Spec Concrete 3000 is a dry, factory blended coarse masonry grout specifically designed for the professional contractor. The proportioning of raw materials and the thorough blending of the product make it superior to conventional sacked concrete products. Standard mix is 6.5 sack, 70% sand and 30% 3/8 aggregate.



of current edition ASTM C476. PMP Spec Concrete 3000 is blended with Type II/V Portland Cement and Washed Aggregates conforming to applicable ASTM standards as well as L.A. City Approval - R.R.24968.

Application: FOR USE IN MASONRY GROUTING APPLICATIONS. Add PMP Spec Concrete 3000 to clean potable water and mix to achieve an 8-inch to 11-inch slump. Approximately 1.4 gallons of water will produce an 8-inch slump. One 90 lb. bag will yield approximately .66 cubic feet.

Uses: PMP Spec Concrete 3000 may be used for a maximum 3000 psi grout for masonry construction.

Advantages:

- High Quality
- Convenience of handling one product
- Excellent for multi-story and difficult access jobs
- Systems that save time and money on labor
- Meets building codes

Packaging: Available in 90 lb. multi wall paper bags, 3000 lb. bulk bags or bulk. Information on silos and bulk systems available upon request.

Technical Data: PMP Spec Concrete 3000 is proportioned in accordance with and meets the performance specifications

Warranty: The technical information and usage statements are based on our best knowledge. The contents of this specification sheet are presented for informational purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.


CAUTION: Contains Portland cement. Prolonged exposure to dust may cause delayed lung disease. Eliminate exposure to dust. Use NIOSH approved mask for silica dust. Freshly mixed materials may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly. If any material gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. See Safety Data Sheet.

For technical support contact:
www.EZMixInc.com jjara@EZMixInc.com

Corporate Office:
11374 Tuxford St.
Sun Valley, CA 91352
(818) 767-8576

Sun Valley Plant:
11450 Tuxford St.
Sun Valley, CA 91352
(818) 768-0568

Rialto Plant:
3355 Industrial Rd.
Rialto, CA 92316
(909) 874-7686

 **WARNING:** This product can expose you to chemicals including Chromium (hexavalent compounds), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.