



E-Z MIX INC.

PMP WALL MUD

Product Name: **PMP WALL MUD**

Data sheet 1300-95
September 2018

Product Description: PMP Wall Mud is a dry, factory blended plaster mix specifically designed for the tile contractor. The control of mix ratio and quality of sand make it a superior product than jobsite mixes. The product is a blend of cement, lime and sand. PMP Wall Mud may be pumped. It may be used for interior or exterior walls. Special orders available.



Application: All substrates must be clean, sound and free from any oil, dust, or bond breakers. Substrates should be damp just prior to application. Apply PMP Wall Mud to clean, potable water and mix to the desired consistency. Maximum thickness per coat is 3/8". Trowel and level into place.

Limitations:

- Do not apply when temperature is below or may fall below 40°F prior to curing.
- Proper curing is required.
- Do not apply to frozen or unsound substrates.
- Do not over water or retemper.

Uses: PMP Wall Mud is used as a float or leveling coat on walls prior to setting tile, marble, brick or veneer.

Advantages:

- Quality control - a consistent batch every time.
- Convenience of handling and transporting one product.
- Excellent for multi-story and difficult access jobs.
- Bulk Systems that save time and labor.

Packaging: Available in 75 lb. multi-wall paper bags, 3000 lb. bulk bags or bulk.

Coverage: Approximately 3 sq. yards per 75 lb. bag when applied at 3/8" thickness.

Technical Data: PMP Wall Mud conforms to IBC, CBC, ANSI, and ASTM requirements as well as L.A. City approval-RR24968.

Warranty: The technical information and usage statements are based on our best knowledge. The contents of this specification sheet are presented for informational purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.

CAUTION: Prolonged exposure to dust may cause delayed lung disease. Eliminate exposure to dust. Use NIOSH approved mask for silica dust. Freshly mixed materials may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly. If any material gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. See Safety Data Sheet.

For technical support contact:
www.EZMixInc.com jjara@EZMixInc.com

Corporate Office:
11374 Tuxford St.
Sun Valley, CA 91352
(818) 767-8576

Sun Valley Plant:
11450 Tuxford St.
Sun Valley, CA 91352
(818) 768-0568

Rialto Plant:
3355 Industrial Rd.
Rialto, CA 92316
(909) 874-7686

 **WARNING:** This product can expose you to chemicals including Chromium (hexavalent compounds), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

©2018 E-Z Mix, Inc.