



CONCRETE GLUE

◆ The Pro's Choice Since 1936



Sakrete® Concrete Glue is a liquid latex bonding adhesive for bonding new concrete, mortar or gypsum plaster to existing surfaces. Eliminates the need for roughing or scoring old surfaces.

Features:

- Ready to use
- No need to roughen or score old surfaces
- Easy to apply

Use For Bonding:

- Concrete
- Mortar
- Gypsum plaster
- Stuccos

Yield/Water/Coverage:

Coverage depends on the porosity and texture of the surface and the method of application.

1 qt (0.95 L)	125 - 200 ft ² (11.6 - 18.6 m ²)
1 gal (3.8 L)	500 - 800 ft ² (46.5 - 74.3 m ²)

Color:

Clear

READ ALL DIRECTIONS BEFORE STARTING WORK

Application:

1. Concrete Glue can be used by applying directly to the repair surface, as a part of a slurry coat mixture or a as partial replacement of water in any cementitious mixture.
2. When applied directly use a paint brush, roller or sprayer. Allow glue to become tacky before applying repair material (usually 10 -60 minutes).
3. When used as part of a slurry coat mixture, mix 3 parts powder to 1 part glue. Smear mixture onto surface to be repaired. Allow mixture to become tacky before applying repair material.

Preparation:

1. Concrete or plaster surfaces should be structurally sound and free of any oil, gas, grease or paint.
2. Concrete surface should be damp but have no standing water
3. Glossy surfaces should be dulled by sanding
4. Gently shake concrete glue pail before use. DO NOT THIN

NOTE: Proper application and installation of all Sakrete products are the responsibility of the end user.

Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). **KEEP OUT OF REACH OF CHILDREN.**

Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.



PROPOSITION 65 WARNING: This product can expose you to ethylene oxide and formaldehyde, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

PROPOSICIÓN 65 ADVERTENCIA: Este producto puede exponerlo a óxido de etileno y formaldehído, que el estado de California considera que causan cáncer. Para más información, vaya www.P65Warnings.ca.gov.