



E-Z MIX INC.

PMP FINE GROUT with Grout Additive

Product Name: **PMP FINE GROUT with Grout Additive**

Data sheet 1204-95
September 2018

Product Description: PMP Fine Grout with Grout Additive is a preblended grout for filling masonry cavities, door frames, and concrete patching and grouting. It is a blend of washed sand, Type II cement 2 1/2:1 and PMP Grout Additive, which gives the mortar fluid properties at a reduced water to cement ratio. It also improves the bond and shrinkage compensation.



strength when placed at an 8-11 inch slump and tested in accordance with ASTM Standards. Recommended water for an 8-11" slump is approximately 8-9 qts. per 94 lb. bag.

Coverage: One 94 lb. bag will yield approximately .85-.90 cubic feet.

Application: Add PMP Fine Grout with Grout Additive to clean potable water and thoroughly mix to the desired slump. Do not over water as this will have a negative effect on strength. Flowing properties are best within the first 30-40 minutes after mix.

Uses: Grout for:

- Concrete Block
- Cavity Walls
- Around window and door frames

Advantages:

- Fluid at low water ratio
- Minimum to no shrinkage
- Superior bonding properties
- Cohesive at high fluidity

Packaging: PMP Fine Grout with Grout Additive is packaged in multi-wall 94 lb. paper bags and 3000 lb. bulk bags. Store in a cool dry area.

Technical Data: PMP Fine Grout with Grout Additive meets ASTM C476. The product is L.A. City Approved - RR24968. PMP Fine Grout with Grout Additive will meet 2500 p.s.i. compressive

Limitations:

- Do not apply when temperatures are expected to fall below 40°F.
- Do not use with other admixtures unless approved in writing by E-Z Mix Inc.

Warranty: The technical information and usage statements are based on our best knowledge. The contents of this specification sheet are presented for informational purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.

CAUTION: Avoid direct contact where possible and wash exposed skin areas promptly. If any material gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. See Safety Data Sheet.

For technical support contact:

www.EZMixInc.com

jjara@EZMixInc.com

Corporate Office:

11374 Tuxford St.
Sun Valley, CA 91352
(818) 767-8576

Sun Valley Plant:

11450 Tuxford St.
Sun Valley, CA 91352
(818) 768-0568

Rialto Plant:

3355 Industrial Rd.
Rialto, CA 92316
(909) 874-7686



WARNING: This product can expose you to chemicals including Chromium (hexavalent compounds), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

©2018 E-Z Mix, Inc.