



E-Z MIX INC.



Product Name: **SPEC MIX® STONE VENEER MORTAR**

Data sheet 1500-08
September 2018

Product Description: SPEC MIX® Stone Veneer Mortar is a dry, factory blended mortar specifically designed for adhered masonry veneer. This product is produced under strict quality control standards.



SPEC MIX Stone Veneer Mortar provides superior bond strength compared to standard masonry mortars. SPEC MIX Stone Veneer Mortar is available in the following standard mix designs:

- SPEC MIX Stone Veneer Mortar (SVM)
- SPEC MIX Stone Veneer Mortar 300 (SVM 300) polymer modified

Uses: SPEC MIX Stone Veneer Mortar is used in the application of adhered masonry veneer or wherever a high bond shear strength mortar is required.

SPEC MIX Stone Veneer Mortar 300 has higher polymer content for increased adhesive properties.

Advantages:

- Quality control - a consistent batch every time
- Excellent for multi-story and difficult access jobs
- Consistent color quality

Packaging: Available in 94 lb. paper bags, 3000 lb. bulk bags and bulk. Information on silos and bulk systems available upon request..

Technical Data: Meets or exceeds the bond shear strength requirements of the IBC, CBC and TMS 402 sections for adhered veneer masonry. Meets 1800 PSI at 28 days when tested according to ASTM C270, Table 2, Type S Mortar.

Coverage: One 94 lb. bag should cover approximately 22 square feet at 1/2" thick.

Limitations:

- Do not apply when temperature is below or may fall below 40°F prior to curing.
- Proper curing is required; extreme weather conditions will affect cure and performance.
- Do not add any admixtures without prior consent from E-Z MIX Inc.

Warranty: The technical information and usage statements are based on our best knowledge. The contents of this specification sheet are presented for informational purposes only and do not constitute responsibility for their use. The manufacturer will replace only that material which is proven defective due to quality of the components of the manufacturing process.

CAUTION: Prolonged exposure to dust may cause delayed lung disease. Eliminate exposure to dust. Use NIOSH approved mask for silica dust. Freshly mixed materials may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly. If any material gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. See Safety Data Sheet.

For technical support contact:
www.EZMixInc.com jjara@EZMixInc.com

Corporate Office:
11374 Tuxford St.
Sun Valley, CA 91352
(818) 767-8576

Sun Valley Plant:
11450 Tuxford St.
Sun Valley, CA 91352
(818) 768-0568

Rialto Plant:
3355 Industrial Rd.
Rialto, CA 92316
(909) 874-7686